

Universal Dual-Path Internet & Cellular Alarm Communicators

(BAT CDMA WIFI & BAT CDMA)

SKU: IPD-BAT-CDMA-WIFI & IPD-BAT-CDMA

ipDatatel's flagship products, the BAT CDMA and the BAT CDMA WIFI, are dual-path Internet & Cellular alarm communicators offering redundant alarm communications with industry-leading remote service capabilities when connected via keybus to supported GE/Caddx, Honeywell, and DSC panels.

Simple Installation - Easy Cellular & Wi-Fi Internet

Wi-Fi configuration via WPS, Internet connection via Ethernet, and pre-activated Cellular with easy wire terminal connection

Verizon CDMA Network

Best nationwide cellular coverage

Universal

Works with most alarm controls featuring Contact ID

Event Notifications

Instant notifications via text/push, email, and computerized voice call

Reduce Service Costs via Virtual Keypad

Eliminate costly truck rolls via remote Virtual Keypad programming when connected via keybus to supported GE/Caddx, Honeywell and DSC panels

Remote Access On the Go

Remotely arm and disarm via Smartphone, tablet and PC. Free SecureSmart™ mobile app with dealer branding and virtual keypad

Downloadable

Upload/Download with supported Honeywell and DSC control panels



INTERACTIVE SERVICES

ipDatatel's SecureSmart™ app with virtual keypad coupled with ipDatatel's cellular and internet alarm communicators can help save time and reduce costs with remote access and on-the-go notifications.



TECHNICAL SPECIFICATIONS

Dual-Path Internet & Cellular Alarm Communicator

(BAT CDMA WIFI & BAT CDMA)

SKU: IPD-BAT-CDMA-WIFI & IPD-BAT-CDMA

CDMA-WIFI

Frequency:

- Wi-Fi 802.11bg (mixed mode)
- Frequencies CDMA 1x 800 MHz/1900 MHz

Power:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

Environmental:

- Temperature Range - 30° to +70°C (- 22° to +158°F)
- Humidity 0 to 95% non-condensing

Physical:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

Security Protocols Supported (Wi-Fi):

- WPA
- WPAII
- WEP

CDMA

Radio:

- Frequencies CDMA 1x 800 MHz/1900 MHz

Power:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

Environmental:

- Temperature Range - 30° to +70° C (- 22° to +158° F)
- Humidity 0 to 95% non-condensing

Physical:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches



CDMA-WIFI
PRODUCT INFO



CDMA
PRODUCT INFO



CONTACT IPDATATEL SALES TODAY

713.452.2700 Ext. 1

866-896-2944 • Sales@ipdatatel.com

Become a registered dealer today ipdatatel.com/newdealer

Purchase ipDatatel's industry-leading devices at one of our partner distributor locations.

ipdatatel.com/distributors

